

Skalflex Fliseklæb

DECLARATION OF PERFORMANCE

No. 68744652

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	68744652
2	INTENDED USE/S	EN 12004-1:2017 Adhesive for ceramic tiles - for internal and external use. Normal setting cementitious adhesive with extended open time.
3	MANUFACTURER:	Sika Danmark A/S Industrivej 20 B 8800 Viborg
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3
6a	HARMONISED STANDARD:	EN 12004-1:2017
	Notified body/ies:	N/A

Declaration of Performance

Skalflex Fliseklæb

68744652

2023.07 , ver. 01

1612

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	A1	System 3	EN 12004-1:2017
Dangerous substances	NPD	System 3	
Adhesion	≥ 0,5N/mm ² after not less than 30 min.	System 3	
Adhesion after heat ageing	≥ 0,5N/mm ²	System 3	
Adhesion after water immersion	≥ 0,5N/mm ²	System 3	
Adhesion after freeze-thaw cycles	≥ 0,5N/mm ²	System 3	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Name
 Function: General Manager
 At place on date of issue

Name : Name
 Function: Technical manager
 At place on date of issue

.....

End of information as required by Regulation (EU) No 305/2011





23

Sika Danmark A/S, Viborg, Denmark

DoP No. 68744652

EN 12004-1:2017

Notified Body N/A

Adhesive for ceramic tiles - for internal and external use

Reaction to fire	A1
Adhesion	$\geq 0,5\text{N/mm}^2$
Adhesion after heat ageing	$\geq 0,5\text{N/mm}^2$
Adhesion after water immersion	$\geq 0,5\text{N/mm}^2$
Adhesion after freeze-thaw cycles	$\geq 0,5\text{N/mm}^2$

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or endusers of the product have been given in good faith based on our own experiences and based of approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Declaration of Performance

Skalflex Fliseklæb
68744652
2023.07 , ver. 01
1612

3/4

BUILDING TRUST



Sika Denmark A/S

Hirsemarken 5
DK-3520 Farum
Denmark
www.sika.dk

Declaration of Performance

Skalflex Fliseklæb
68744652
2023.07 , ver. 01
1612

4/4

BUILDING TRUST

