
Skalflex Gulvpartel Fin

DECLARATION OF PERFORMANCE

No. 41614429

| | | |
|----|--|--|
| 1 | UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE: | 41614429 |
| 2 | INTENDED USE/S | EN 13813:2003 Cementitious screed material for internal use |
| 3 | MANUFACTURER: | Sika Danmark A/S Industrivej 20 B 8800 Viborg |
| 4 | AUTHORISED REPRESENTATIVE: | |
| 5 | SYSTEM/S OF AVCP: | System 4 |
| 6a | HARMONISED STANDARD: | EN 13813:2003 |
| | Notified body/ies: | N/A |

Declaration of Performance

Skalflex Gulvpartel Fin
41614429
2023.04 , ver. 01
1612

7 DECLARED PERFORMANCE/S

| Essential Characteristics | Performance | AVCP | Harmonised Technical Specification |
|---------------------------------|------------------|----------|------------------------------------|
| Reaction to fire | A1 _{fi} | System 4 | EN 13813:2003 |
| Release of corrosive substances | CT | System 4 | |
| Water permeability | NPD | System 4 | |
| Water vapour permeability | NPD | System 4 | |
| Compressive strength | C25 | System 4 | |
| Flexural strength | F7 | System 4 | |
| Sound insulation | NPD | System 4 | |
| Sound absorption | NPD | System 4 | |
| Thermal resistance | NPD | System 4 | |
| Chemical resistance | NPD | System 4 | |

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Name
 Function: Corporate TM Manager
 At place on date of issue

Name : Name
 Function: CPE
 At place on date of issue

.....

End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

Skalflex Gulvspartel Fin
 41614429
 2023.04 , ver. 01
 1612





23

Sika Danmark A/S, Viborg, Denmark

DoP No. 41614429

EN 13813:2003 CT-C25-F7

Notified Body N/A

Cementitious screed material for internal use

| | |
|---------------------------------|------------------|
| Reaction to fire | A1 _{fl} |
| Release of corrosive substances | CT |
| Compressive strength | C25 |
| Flexural strength | F7 |

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Skalflex Gulvspartel Fin
41614429
2023.04 , ver. 01
1612

Sika Denmark A/S
Hirsemarken 5
DK-3520 Farum
Denmark
www.sika.dk

Declaration of Performance

Skalflex Gulvspartel Fin
41614429
2023.04 , ver. 01
1612

4/4

BUILDING TRUST

