according to Regulation (EC) No. 1907/2006

Skalflex Pudsemørtel KC 50/50/700 0-2mm



Date of last issue: -

Revision Date: 16.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Version 1.0

1.1 Product identifier

Trade name Skalflex Pudsemørtel KC 50/50/700 0-2mm

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Cement / Mortar

1.3 Details of the supplier of the safety data sheet

Company name of supplier Sika Danmark A/S

Hirsemarken 5 3520 Farum

Telephone : +45 48 18 85 85 E-mail address of person : EHS@dk.sika.com

responsible for the SDS

1.4 Emergency telephone number

Giftlinjen (Bispebjerg Hospital) telefon 82 12 12 12

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word Danger

Hazard statements H315 Causes skin irritation.

> H318 Causes serious eye damage.

P101 If medical advice is needed, have product Precautionary statements

container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

Prevention:

P264 Wash skin thoroughly after handling.

Wear protective gloves/ eye protection/ face P280

according to Regulation (EC) No. 1907/2006

Skalflex Pudsemørtel KC 50/50/700 0-2mm

Print Date 26.03.2024

Date of last issue: -

Revision Date: 16.03.2024

protection.

Version 1.0

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

Hazardous components which must be listed on the label:

Cement (chromium reduced)

2.3 Other hazards

The content of soluble Chromium (VI) is not greater than 0,0002% in accordance with Annex XVII, Paragraph 47 of the EU Regulation 1907/2006.

The product reacts highly alkaline with water.

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		,
Cement (chromium reduced)	65997-15-1	Skin Irrit. 2; H315	>= 5 - < 10
	266-043-4	Eye Dam. 1; H318	
		STOT SE 3; H335	
		(Respiratory system)	
calcium dihydroxide	1305-62-0	Skin Irrit. 2; H315	>= 5 - < 10
-	215-137-3	Eye Dam. 1; H318	
	01-2119475151-45-	STOT SE 3; H335	
	XXXX	(Respiratory system)	
Flue dust, portland cement	68475-76-3	Skin Irrit. 2; H315	>= 1 - < 2,5
	270-659-9	Eye Dam. 1; H318	
	01-2119486767-17-	STOT SE 3; H335	
	XXXX		

according to Regulation (EC) No. 1907/2006

Skalflex Pudsemørtel KC 50/50/700 0-2mm



Revision Date: 16.03.2024 Version 1.0 Print Date 26.03.2024

Date of last issue: -

Substances with a workplace exposure limit :			
Quartz (SiO2)	14808-60-7 238-878-4		>=80

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

Causes skin irritation.

Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

according to Regulation (EC) No. 1907/2006

Skalflex Pudsemørtel KC 50/50/700 0-2mm



Date of last issue: -

SECTION 5: Firefighting measures

5.1 Extinguishing media

Revision Date: 16.03.2024

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

ucts

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

6.2 Environmental precautions

Try to prevent the material from entering drains or water Environmental precautions

courses.

No special environmental precautions required.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Pick up and arrange disposal without creating dust.

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

according to Regulation (EC) No. 1907/2006

Skalflex Pudsemørtel KC 50/50/700 0-2mm



Date of last issue: -

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Avoid dust formation. Provide appropriate exhaust ventilation

at places where dust is formed.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Further information on stor-

age stability

Keep in a dry place.

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *	
Quartz (SiO2)	14808-60-7	GV (Respirable dust)	0,1 mg/m3 (Silica)	DK OEL	
	Further inforr	Further information: Means that the substance is included in the			
	list of substa	list of substances considered carcinogenic., List of limit values for			
	dust.	dust.			
		GV (total)	0,3 mg/m3 (Silica)	DK OEL	
		GV (respirable)	0,1 mg/m3 (Silica)	DK OEL	
	Further inforr	Further information: Means that the substance is included in the			
	list of substa	list of substances considered carcinogenic.			
		S (total powder and dust)	0,6 mg/m3 (Silica)	DK OEL	
		S (inhalable fraction)	0,2 mg/m3 (Silica)	DK OEL	
calcium dihydroxide	1305-62-0	TWA (Respirable fraction)	1 mg/m3	2017/164/EU	
	Further inforr	Further information: Indicative			
		STEL (Respirable fraction)	4 mg/m3	2017/164/EU	
		GV	5 mg/m3	DK OEL	
		GV (respirable fraction)	1 mg/m3	DK OEL	
		S	10 mg/m3	DK OEL	
		S (inhalable fraction)	4 mg/m3	DK OEL	

according to Regulation (EC) No. 1907/2006

Skalflex Pudsemørtel KC 50/50/700 0-2mm



Revision Date: 16.03.2024 Version 1.0 Print Date 26.03.2024

Date of last issue: -

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

general dust value

Form of exposure	Peak-limit: excursion factor (category)	Value type	Control parameters	Basis
Total dust		GV	3 mg/m3	DK OEL
Dust		GV	0,5 mg/m3	DK OEL
Respirable dust		GV	5 mg/m3	DK OEL
Dust		GV	10 mg/m3	DK OEL

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Skin and body protection : Dust impervious protective suit

Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

particulate filter P

P1: Inert material: P2. P3: hazardous substances

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Try to prevent the material from entering drains or water

courses.

No special environmental precautions required.

according to Regulation (EC) No. 1907/2006

Skalflex Pudsemørtel KC 50/50/700 0-2mm

Print Date 26.03.2024

Revision Date: 16.03.2024 Version 1.0

Date of last issue: -

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state solid Appearance powder Colour grey Odour odourless

Melting point/range / Freezing :

No data available

Boiling point/boiling range No data available

Flammability (solid, gas) No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit /

Lower flammability limit

No data available

No data available Flash point

Auto-ignition temperature No data available

Decomposition temperature No data available

pΗ No data available

Viscosity

Viscosity, kinematic No data available

Solubility(ies)

Water solubility No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure No data available

Density No data available

Relative vapour density No data available

Particle characteristics No data available

9.2 Other information

No data available

according to Regulation (EC) No. 1907/2006

Skalflex Pudsemørtel KC 50/50/700 0-2mm

Print Date 26.03.2024

Date of last issue: -

Revision Date: 16.03.2024

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

Version 1.0

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

Skalflex Pudsemørtel KC 50/50/700 0-2mm

Print Date 26.03.2024

Date of last issue: -

Revision Date: 16.03.2024

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

Version 1.0

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

Skalflex Pudsemørtel KC 50/50/700 0-2mm



Date of last issue: -

12.7 Other adverse effects

Revision Date: 16.03.2024

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 17 01 01 concrete

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006

Skalflex Pudsemørtel KC 50/50/700 0-2mm

Print Date 26.03.2024

Revision Date: 16.03.2024

Date of last issue: -

IATA (Cargo) : Not regulated as a dangerous good IATA (Passenger) Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

: Not applicable

- registered by us, and/or

- excluded from the regulation, and/or

Version 1.0

- exempted from the registration.

REACH - Restrictions on the manufacture, placing on

the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

REACH - Candidate List of Substances of Very High None of the components are listed

Concern for Authorisation (Article 59). (=> 0.1 %).

REACH - List of substances subject to authorisation Not applicable

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-Not applicable plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-Not applicable

tants (recast)

Regulation (EU) No 649/2012 of the European Parlia-

: Not applicable ment and the Council concerning the export and import

of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds Law on the incentive tax for volatile organic compounds

according to Regulation (EC) No. 1907/2006

Skalflex Pudsemørtel KC 50/50/700 0-2mm

Print Date 26.03.2024

Date of last issue: -

Revision Date: 16.03.2024

(VOCV)

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Version 1.0

Not applicable

MAL-Code-Number : 00-4 (1993)

Product registration number : 4166375

GISCODE : ZP1

Waste Group : X

Reference : Arbejdstilsynets bekendtgørelse nr. 301 af 13. maj 1993 om

fastsættelse af kodenumre.

Bekendtgørelse nr. 21 af 16. januar 1996 af lov om kemiske

stoffer og produkter.

Arbejdstilsynets bekendtgørelse nr. 1793 af 18/12/2015 om arbejde med stoffer og materialer (kemiske agenser).

Bekendtgørelse nr. 1794 af 18/12/2015 om særlige pligter for

fremstillere, leverandører og importører mv. af stoffer og materialer efter lov om arbejdsmiljø.

Arbejdstilsynets bekendtgørelse nr. 239 af 6. april 2005 om

unges arbeide.

uriges arbejue.

Miljøstyrelsens bekendtgørelse nr. 1369 af 25/11/2015 om

begrænsning af VOC.

AT-Vejledning C.0.1 August 2007: Grænseværdier for stoffer

og materialer.

EU forordningen 1907/2006 (REACH). EU forordningen 1272/2008 (CLP).

Bekendtgørelse nr. 48 af 13/01/2010 om affald. EU forordning 453/2010 (Opdatering til CLP).

Other regulations:

Young people under the age of 18 are not allowed to use or be exposed to the product professionally. Young people above the age of 15 are, however, except from this rule if the product is a necessary part of their education.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H315 : Causes skin irritation.

according to Regulation (EC) No. 1907/2006

Skalflex Pudsemørtel KC 50/50/700 0-2mm



Date of last issue: -

Revision Date: 16.03.2024

H318 : Causes serious eye damage. H335 : May cause respiratory irritation.

Full text of other abbreviations

Eye Dam. : Serious eye damage

Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a

fourth list of indicative occupational exposure limit values

DK OEL : Denmark. Occupational Exposure Limits

2017/164/EU / STEL : Short term exposure limit
2017/164/EU / TWA : Limit Value - eight hours
DK OEL / S : Exposure period of 15 minutes
DK OEL / GV : Long term exposure limit

ADR : European Agreement concerning the International Carriage of

Version 1.0

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Skin Irrit. 2 H315 Calculation method Eye Dam. 1 H318 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

according to Regulation (EC) No. 1907/2006

Skalflex Pudsemørtel KC 50/50/700 0-2mm

Print Date 26.03.2024

Revision Date: 16.03.2024 Version 1.0

Date of last issue: -

Changes as compared to previous version!

DK / EN